



**LOW PROFILE
30" CURB & GUTTER
TYPE D**

N.T.S.

NOTES:

1. TYPE D CURB AND GUTTER IS ONLY ALLOWED AS AN OPTION ON LOCAL (45' R.O.W.) STREETS IN THE R-1, R-2-1, R-2-2, & R-3-1 RESIDENTIAL ZONES.
2. WHERE SIDEWALKS CROSS DRIVEWAY APPROACHES BEHIND A TYPE D CURB & GUTTER, MINIMUM SIDEWALK THICKNESS SHALL BE 6" THICK REINFORCED WITH #4 BARS @ 16" O.C. BOTH WAYS. SIDEWALKS IN OTHER AREAS SHALL BE A MINIMUM OF 4" THICK..

NOTE:

- ALL CURB AND GUTTER TYPES SHALL HAVE:
1. CONSTRUCTION JOINTS EVERY 10' O.C. 1/2" DEEP.
 2. EXPANSION JOINTS AT THE P.C. AND P.T. OF A STREET INTERSECTION CURB RADIUS RETURN.

SHEET NO.
C1A
FILE: C01A

LOW PROFILE
CURB & GUTTER (TYPE D)

REVISIONS		
DATE	DESCRIPTION	BY
7/2021	DETAIL C1A ADDED TO STANDARDS	J.A.S.

CEDAR CITY
10 NORTH MAIN STREET
CEDAR CITY, UTAH 84720
PH. (435) 586-2863

SCALE: N.T.S.
DRAWN: T.B.M.

DATE: 7/2021
CHECKED: J.A.S.